

# SPUR HRX

	ISO	希釈	時間
ADOX CHS 100 II	100/21°	1 + 17	11
ADOX Silvermax	50/18°	1 + 20	10
AGFA APX 100 New	64/19°	1 + 20	10
AGFA APX 400 New	320/26°	1 + 17	15
Fomapan 100	100/21°	1 + 20	11,5
Fomapan 200	125/22°	1 + 17	9
Fomapan 400	200/24°	1 + 11	13
Fuji Acros 100	64/19°	1 + 20	11
Ilford Delta 100	80/20°	1 + 20	8,5 - 9
Ilford Delta 400	250/25°	1 + 15	13
Ilford Delta 3200	800/30°	1 + 8	15
Ilford Pan F +	32/16°	1 + 20	8,5
Ilford FP4 +	100/21°	1 + 20	9,5
Ilford HP5 +	400/27°	1 + 17	11
Ilford SFX 200	80/20°	1 + 17	10
Kentmere 100	80/20°	1 + 20	9,5
Kentmere 400	400/27°	1 + 13	14
Kodak Tmax 100	64/19°	1 + 17	11,5
Kodak Tmax 400	320/26°	1 + 20	12,5
Kodak Tri X 400	250/25°	1 + 17	11
ORWO UN 54	80/20°	1 + 17	9,5
Rollei Retro 100	64/19°	1 + 20	10
Rollei Retro 400	320/26°	1 + 17	15
Rollei Superpan 200	40/17°	1 + 11	12
Rollei Retro 400 S	40/17°	1 + 11	12
Rollei IR 400 S	40/17°	1 + 11	12
Rollei Retro 80 S	20/14°	1 + 17	8
Rollei Retro 100 Tonal	64/19°	1 + 13	13
Rollei RPX 25	20/14°	1 + 20	10
Rollei RPX 100	100/21°	1 + 17	12
Rollei RPX 400	400/27°	1 + 9	15

攪拌 : 2x/60/1 最初に2回倒立攪拌後、60秒待ち、その後1回反転させます。